FENCE AND WALL GUIDELINES FOR MF 4


I. GENERAL

FENCE TYPES AND LOCATIONS:

This fencing guideline is part of the sales contract package for each Home Owner. This guideline defines the types and heights of fences and walls that will be permitted on the individual lots. These guidelines must be followed when considering the construction of fences and walls. Copies of these guidelines are on file with the Royal Kunia Community Association Design Committee (RKCADC).

Sketch "A" illustrates fence types and locations by lines and symbols that correspond to a "Fencing Legend". For any given symbol in a specific location, the fence and wall heights are stated as the maximum allowable. Fences and walls may be constructed lower than the maximum heights stated.

The fencing plans also show the maximum boundary for each fence type. The homeowner has the option of constructing a fence of the designated type anywhere from the front plane of the house as the maximum boundary line shown.



TYPICAL LOT FENCE PLAN

Sketch "A"

Applies to Lots: 2-5, 9-12, 15-19, 40-46, 49-56, 60-68, 70, 72-85

II ACCEPTABLE WALL OR FENCE BUILDING MATERIAL

The following materials are allowed for the construction of fences and walls within a homeowner's property.

WALLS:

Walls may be constructed of only the following materials:

- Concrete masonry unit (CMU, hollow tile block) block with plaster or stucco coating on the visible side (from the street or neighboring property)
- CMU block wall including split face with texture side facing the street or neighboring property. Split face CMU with texture is considered finish and does not require plaster or stucco finish.
- Natural stone or stone veneer (no coral).


FENCING:

Fencing may be constructed of only the following materials:

- Wrought Iron
- Steel Tubing
- Anodized aluminum
- Redwood/Cedar Wood
- Vinyl Fencing (in approved colors-white, beige, gray)

RETAINING WALLS DESIGN

- A. Solid or picket fencing is permitted for front yard fences not to exceed two feet, six inches (2'-6") in height as measured from the level of the area immediately on the exterior side of the proposed fence, facing the street or neighboring property.
- B. All fences constructed atop front yard retaining walls or side yard retaining walls on corner lots are subject to the following:
 - 1. Solid fences of any kind is not permitted. Only picket type fences shall be permitted.
 - 2. The dimension of any picket shall not exceed two inches by two inches and the maximum spacing between the pickets is what is allowed by the building code (currently set at four (4) inches).
 - Columns and/or support posts located at intervals between the pickets shall not exceed the dimension of eight (8) inches by eight (8) inches and shall not be spaced closer than six (6) feet.
 - 4. See Sketch "B" for details.



Sketch "B"

ACCEPTABLE FENCE DESIGNS - CITY AND COUNTY APPROVAL

As required by the City and County of Honolulu's Department of Planning and Permitting (DPP), fence designs must conform to the "Land Use Ordinance" on file at the DPP offices. All fences will require a building permit. The fence types and material dimensions must be followed exactly to ensure approval from the DPP. Deviations from these DPP approved designs will result in building permit applications being denied.

III ROYAL KUNIA MF 4 FENCE REQUIREMENT WITHIN THE LOTS

Royal Kunia MF 4 have special provisions for front, side and back yard walls and fences.


- 1. Solid or picket fencing is permitted for front yard fences not to exceed two feet, six inches (2'-6") in height as measured from the level of the area immediately on the exterior side of the proposed fence, facing the street or neighboring property.
- 2. FRONT YARD: For the purposes of these guidelines, a front yard shall be defined as being that portion of the yard bounded by a street up to the front plane of the house or garage. For corner lots, see "Corner Lots" section for front yard definition. Fences and /or walls in the front yard shall be governed by the following:
 - A. Any walls or fence installed by the homeowner shall not exceed 2'-6" in height measured from the existing finish grade to the top of the wall or fence.

Exception:

If the difference in grade between the adjacent sidewalk and the finish floor of the house slab exceeds 42", then a retaining wall may be created. The top of this retaining wall shall not exceed an elevation that is 12" lower than the finish floor of the house slab.

A fence may be added on top of this retaining wall. This fence shall not exceed 42" in height from the top of the retaining wall.

The fence or wall, it shall not impede any sight lines that are required for traffic safety.



See Sketch "C"

Sketch "C"

- B. Trash enclosure is permitted behind the front plane of the house.
- C. Refer to Sketch "A" for fence and wall height locations on typical lots.
- 2. REAR & SIDE YARDS: For purposes of these guidelines, a rear yard shall be defined as a yard at the opposite end of a lot from the front yard, except in the case of corner lots. All other yard not defined as front or rear yards shall be treated as side yards. Fences and/or walls in the rear and the side yards shall be governed by the following:

- A. The following restrictions apply to lots where the surroundings grade condition is minimal such that it does not require a retaining wall. Fences and walls starting along the front plane of the house extending to the side property lines and along the side property lines extending back from the front plane of the house or garage and all rear yard fences shall not exceed six (6) feet in height. (See Sketch "A"). The Wall or fence may be made of one material or may be partly wall and partly fence, each to be made of one material only.
- B. If the surrounding grade condition of a lot requires a retaining wall, the following restrictions shall apply. Retaining walls which run along the side property lines extending back from the front plane of the house or garage and all rear yard retaining walls shall not exceed a height as described in Section 3.40 of the Land Use Ordinance, as the same may be amended from time to time. See Sketch "E"
- Refer to Sketch "A" for fence and wall height locations on typical lots.
- D. Lots located adjacent to the open space area on MF-4's west side may have a type "B" fence along the open space side only. The lots are numbers 6, 7, 8, 20, 21, 22, 37, 38, 39, 57, 58, and lot 59.
- 3. CORNER LOTS: Corner lots have streets along two or more adjacent sides and thus technically have more than one front yard. For the purpose of these guidelines, the front yard shall be considered the yard adjacent to the street from which the garage and /or the house is entered. All other yards shall be treated as side yards.

On corner lots, walls, fences or vegetation may not be constructed, placed or maintained at a height greater the two (2) feet, six (6) inches within the sight line designated by the City & County of Honolulu Department of Transportation Services, as shown on the plot plan for the subject lots.

- 4. FLAG LOTS: Flag Lots with unusual fence and/or wall conditions along the property lines will be issued an individual fence guide
- FENCE MATERIAL: See Section II Acceptable Wall or Fence Building Material, Fencing.

IV SPECIAL CONSIDERATIONS AND CONDITIONS

EASEMENTS WITHIN A HOMEOWNER'S PROPERTY

Any wall or fence, regardless of yard designation, must be placed in back of any utility, landscape or sight line easements existing within an owner's property. It is important that any required footings also fall outside of any easement line. Walls and fences built over and into easement lines may result in the wall or fence being removed at the homeowner's expense.


WALL SHARING WITH ADJACENT OWNERS

Any wall or fence installed by a homeowner must be constructed entirely within his/her own property, unless a written agreement is made with an adjacent property owner to share ownership of the wall or fence. It is the recommendation of Kunia Residential Partners that homeowners install any fences or walls entirely within one homeowner's lot. Cost sharing between neighbors will be left entirely between neighbors, with no intervention from the Developer.

PARALLEL WALLS (two walls built along side one another on neighboring properties.).

It is the position of the Design Committee that construction of parallel walls not be encouraged because they contribute to visual clutter. However, due to the varying needs of adjacent neighbors, parallel walls may be approved on a case-by-case basis proving the following conditions are met:

- The parallel walls shall not go beyond the front plane of the applicant's home.
 The front plane of the home shall include the garage/carport at one side of the residence.
- 2. All parallel walls along side yards shall have a perpendicular wall of the same material returning a minimum of five (5) feet toward the house. This five (5) feet return may include a gate.
- 3. Parallel walls shall be encouraged to be the same height. However, because of differences in grades between properties and different family requirements among property owners, parallel walls of different heights may be approved on a case-by-case basis. (See Sketches "D1", "D2", and "D3")




Parallel walls are permitted when there is a difference in grade and one neighbor's wall is retaining for it's full height so that a guardrail is needed on the higher elevation.

Sketch "D1"

Between these parallel walls, a landscaped planter is created which visually lowers the combined heights of the two walls.





Wall of the same material turned ninety (90) degrees to the front face of the residence.

Parallel walls

Along the side yard parallel walls shall have a perpendicular wall of the same material returning a minimum of five (5) feet towards the house. This five (5) feet may include a gate.

Sketch "D3"

JOINT OWNERSHIP AND MAINTENANCE AGREEMENT

Royal Kunia MF-4 Fence and Wall Guidelines Whenever two adjacent owners desire to jointly construct a fence or wall along and over the property line, it is recommended that a joint agreement for construction and maintenance be signed.

SIDEWALKS AND CURBS

Fences and walls and its footings shall be set back from sidewalks, curbs and property lines as indicated on the plot plans. It is very important that homeowners be aware of their property and easement lines.

STREET TREES

Street trees are illustrated on the individual plot plans provided to homeowners as part of the sales contract package. These trees have been planted per City and County requirements. Homeowners shall not remove trees and shall be responsible for maintaining (watering) the trees.

SIGHT LINE SETBACKS

The City and County of Honolulu's Department of Transportation Services has established sight line setbacks for certain lots within MF 4. The Department of Transportation Services sight line setbacks supersede all other setbacks. No fence which projects more than 2'-6" above existing grade established when lot was conveyed from Seller to Buyer shall be constructed within roadway sight lines.

It is the responsibility of the homeowner to verify that all proposed fence or wall locations do not conflict with possible sight line easements.


RETAINING WALLS AT SLOPE CONDITIONS

For those lots with slope banks within their yard, see Sketch "C" and "E".


OTHER REQUIREMENTS

Prior to commencing any fence or wall construction, homeowners must first obtain a written approval of "Expressions at Royal Kunia Community Association Design Committee", the "Royal Kunia Community Association Design Committee", and must also meet the requirements of the Land Use Ordinance of the City and County of Honolulu and any other City, State, or County requirements necessary to secure a building permit.


Any improvements constructed without first obtaining the "Expressions at Royal Kunia Community Association Design Committee", the "Royal Kunia Community Association Design Committee", and the City's Department of Land Utilization approval may be subject to fines and/or removal by the Expressions at Royal Kunia Community Association at the homeowner's expense.




RETAINING WALL PROTECTING A CUT




RETAINING WALL CONTAINING FILL




CUT and FILL RETAINING WALL



TERRACED RETAINING WALLS





RETAINING WALLS WITH SAFETY RAILINGS

CITY & COUNTY OF HONOLULU -Land Use Ordinance RETAINING WALL GUIDELINES Sketch "E"


Note: See the City & County's Land Use Ordinance Section 3.4 for details.

Royal Kunia MF-4 Fence and Wall Guidelines

March 15, 2000



- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight line setback of the roadway, as indicated on the plan.



NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence Plan

for house at:

E Model Site

100 Kahelu Ave Millani, Hawaii

Date: November 12, 1999

Kunia	Residential Partners	P.O. Box 898900
FRONTYARD	30° OR E	ROCK WALL
CORNER LOT	OPEN RALL W/ SOUD BASE OPEN OPEN	FENCE ELEVATIONS NOT TO SCALE
OR SIDEYARD	BOARD FENCE BLOCK	WALL ROCK WALL

ACCEPTABLE FENCE BUILDING MATERIALS

- FRONT YARD FENCE maximum height 30"

 Picket Fence wood or vinyl

 Block Wall with plaster or stucco

 Rock Wall dark mass rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Roil

- Open Roll with Solid Base lower portion up to 30" height.

 Where stated on plan, total fence height may be 6"-0".

BACKYARD & SIDEYARD FENCE


- Board Fence wood or vinyl
 Block Wall with plaster or stucco.
 Rock Wall dark moss rock with dark colored grout.
- FENCE SYMBOL LEGEND ----- FRONT YARD FENCE CORNER LOT FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- · Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Seller's Signature:_ Purchaser's Signature: _ Date: _ Purchaser's Signature: _ Date:_

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sightline setback of the roadway, as indicated on the plan.





..... OPEN SPACE EDGE FENCE

OPEN SPACE EDGE FENCING NOTE:

- FENCING ADJACENT TO THE OPEN SPACE AREA OF THE LOT SHALL HAVE NO CONTINOUS SOUD FOOTINGS.
- THE ONLY ACCEPTABLE FENCE TYPE FOR THE OPEN SPACE EDGE IS THE OPEN RAIL FENCING WITH A MAXIMUM HEIGHT OF 6 FEET.

Honolulu, Hawaii

NOTE:

SIDEYARD

OR

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Kunia Residential Partners

BOARD FENCE

Fence Guideline Plan

P.O. Box 2780

FENCE

ELEVATIONS NOT TO SCALE ROCK WALL

for house at:

BR Model 6 Lot

2000

PICKET FENCE BLOCK WALL ROCK WALL FRONTYARD 101 CORNER

BLOCK WALL

ACCEPTABLE FENCE BUILDING MATERIALS

650 Iwilei Rd.

FRONT YARD FENCE maximum height 30"

Picket Fence — wood or viny!

Block Wall — with plaster or stucco

Rock Wall — dark moss rock with

dark colored grout TYPE "B" - maximum height 5'-0"

Open Rail Open Rail with Solid Base — lower portion up to 30" height

Where stated on plan, total fence height may be 6'-0".

FENCE SYMBOL LEGEND - - FRONT YARD FENCE CORNER LOT FENCE BACK OR SIDE FENCE

Date: February 18,


TYPE "C" - maximum height 6'0"


Board Fence — wood or vinyl
Black Wall — with plaster or stucco.
Rock Wall — dark moss rock with dark colored grout.

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
 Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neghboring property

_ Date: _ Purchaser's Signature: ___ Seller's Signature:_ Date: _ Purchaser's Signature: ___ Date:





- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight—line setback of the roadway, as indicated on the plan.

NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Fence Guideline Plan

for house at:

Model DR Site

Kunia Residential Partners

P.O. Box 898900

100 Kahelu Ave Militani, Hawaii

March 07, 2000 Date:

FENCE SYMBOL LEGEND

----- FRONT YARD FENCE

- CORNER LOT FENCE

BACK OR SIDE FENCE

BLOCK WALL PICKET FENCE FRONTYARD E OPEN RAIL W, OPEN RAIL 201 CORNER FENCE ELEVATIONS BOARD FENCE BLOCK WALL ROCK WALL SIDEYARD F BACK

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- Picket Fence wood or vinyl Block Wall with plaster or stucco Rock Wall dark moss rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Rail

- Open Rail with Solid Base lower portion up to 30" height

 Where stated on plan, total
- fence height may be 6'-0".

· Balastrade BACKYARD & SIDEYARD FENCE maximum height 6'0" Board Fence — wood or vinyl Block Wall — with plaster or stucco. Rock Wall — dark mass rock with dark colored grout.

- · Chainlink Fence or any Wire Mesh

UNACCEPTABLE FENCE


BUILDING MATERIALS

· Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
Oate:	Purchaser's Signature:	Date:



- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sightline setback of the roadway, as indicated on the plan.



This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent NOTE: the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence Plan

for house at:


Ε Model Site Lot

Kunia Residential Partners

P.O. Box 898900

100 Kahelu Ave Mililani, Hawaii

Date: February 18, 2000



ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- FRONT YARD FENCE.
 maximum height 30"
 Picket Fence wood or vinyl
 Block Wall with plaster or stucco
 Rock Wall dark moss rock with

dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0'
• Open Rail

- · Open Rail with Solid Base lower
- portion up to 30" height Where stated on plan, total fence height may be 6'-0".

BACKYARD & SIDEYARD FENCE maximum height 6'0"

Board Fence – wood or vinyl

Block Wall – with plaster or stucco.

Rock Wall – dark moss rock with

- dark colored grout.


FENCE SYMBOL LEGEND ----- FRONT YARD FENCE TYPE B FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- · Chainlink Fence or any Wire Mesh
- Unfinished CMU visible from the street or neighboring property

Seller's Signature:_ Purchaser's Signature: _ Date: . Date: Purchaser's Signature: .

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shored.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight— line setback of the roadway, as indicated on the plan.



NOTE:

F

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence Plan for house at:

BR Model Site 13 Lot

Kunia Residential Partners

P.O. Box 898900

100 Kahelu Ave Mililani, Hawaii

Date: November 12, 1999

FENCE SYMBOL LEGEND

---- FRONT YARD FENCE

- I - I - CORNER LOT FENCE

BACK OR SIDE FENCE

PICKET FENCE BLOCK WALL ROCK WALL FRONTYARD OPEN RAIL W/ OPEN RAIL CORNER LOT **ELEVATIONS** NOT TO SCALE BLOCK WALL SIDEYARD

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE maximum height 30"

Picket Fence — wood or vinyl

Block Wall — with plaster or stucco

Rock Wall — dark moss rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"

- Open Rail Open Roll with Solid Base – lower portion up to 30" height
 Where stated on plan, total fence height may be 6"-0".


BACKYARD & SIDEYARD FENCE

Back TARD & SIDE TARD FENCE,
maximum height 6"0"
Board Fence — wood or vinyl
Block Wall — with plaster or stucco.
Rock Wall — dark moss rock with
dark colored grout.

- Chainlink Fence any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
Date:	Purchaser's Signature:	Date:

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sightline setback of the roadway, as indicated on the plan.



TRUE NORTH

NOTE:

F

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.




Guideline Fence Plan for house at:

C Model Site Lot 14

Kunia Residential Partners

100 Kahelu Ave Mililani, Hawaii

Date: November 12, 1999



ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- FRONT YARD FENCE
 maximum height 30"
 Picket Fence wood or vinyt
 Block Wall with plaster or stucco
 Rock Wall dark moss rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Roil

- Open Rail with Solid Base lower portion up to 30" height
 Where stated on plan, total fence height may be 6'-0".

BACKYARD & SIDEYARD FENCE

- BACKYAND & SIDETAND FENCE maximum height 6'0"

 Board Fence wood or vinyl

 Block Wall with plaster or stucco.

 Rock Wall dark mass rock with dark colored grout.


FENCE SYMBOL LEGEND ---- FRONT YARD FENCE - I - I - CORNER LOT FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- · Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Seller's Signature:_ Purchaser's Signature: ___ Date: _ Date:_ Purchaser's Signature: _ Date: .

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sightline setback of the roadway, as indicated on the plan.



NOTE:

F

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Fence Guideline Plan

for house at:

C Model Site Lat 14 Date: November 12, 1999

Kunia Residential Partners 100 Kahelu Ave Mililani, Hawaii P.O. Box 898900 BLOCK WALL FRONTYARD F or I OR OPEN RAIL W/ OPEN RAIL LOI CORNER FENCE ELEVATIONS NOT TO SCALE BOARD FENCE BLOCK WALL ROCK WALL SIDEYARD

I

T - 3

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- PROFIT TARD FERGE
 maximum height 30"
 Picket Fence wood or vinyt
 Block Wall with plaster or stucco
 Rock Wall dark moss rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Rail

- Open Rail with Solid Base lower portion up to 30" height
 Where stated on plan, total fence height may be 6"-0".


BACKYARD & SIDEYARD FENCE maximum height 6'0"

Board Fence — wood or viny

Block Wall — with plaster or stucco.

Rock Wall — dark mass rock with

- dark colored grout.




UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- · Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Seller's Signature:_ Purchaser's Signature: __ _ Date: _ Date: Date: Purchaser's Signature:.

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight—line setback of the roadway, as indicated on the plan.



NOTE:

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Fence Plan

Guideline for house at:

Model В Site Lot 20

Kunia Residential Partners

P.O. Box 898900

100 Kahelu Ave Mililani, Hawaii


Date: March 21, 2000

FENCE SYMBOL LEGEND

----- FRONT YARD FENCE

CORNER LOT FENCE

BACK OR SIDE FENCE



ACCEPTABLE FENCE BUILDING MATERIALS

- FRONT YARD FENCE maximum height 30"
 Picket Fence wood or viny!
 Block Wall with plaster or stucco
 Rock Wall dark moss rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Rail

Open Rail Open Rail with Solid Base — lower portion up to 30° height Where stated on plan, total fence height may be 6'-0".

- BACKYARD & SIDFYARD FENCE maximum heigh: 500"

 Board Fence wood or vinyl


 Block Wall with plaster or stucco.


 Rock Wall dark moss rock with dark colored grout.

UNACCEPTABLE FENCE BUILDING MATERIALS

- Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Seller's Signature: Purchaser's Signature: _ Date: Date:_ Purchaser's Signature: . Date:





- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight—line setback of the roadway, as indicated on the plan.

NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Seller's Signature:_

Date:

Guideline Fence Plan for house at:

C Model Site

P.O. Box 898900 100 Kahelu Ave Kunia Residential Partners PICKET FENCE BLOCK WALL ROCK WALL FRONTYARD OPEN RAIL SOUD BASE OPEN RAIL 5 CORNER FENCE **ELEVATIONS** NOT TO SCALE BLOCK WALL BOARD FENCE SDEYARD F BACK

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

Mililani, Hawaii

FRONT YARD FENCE
maximum height 30"
Picket Fence — wood or vinyl
Block Wall — with plaster or stucco
Rock Wall — dark moss rock with
dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0'
• Open Rail

- Open Rail with Solid Base lower portion up to 30" height
- Where stated on plan, total fence height may be 6'-0".

UNACCEPTABLE FENCE BUILDING MATERIALS

March 21, 2000

FENCE SYMBOL LEGEND

---- FRONT YARD FENCE

CORNER LOT FENCE

BACK OR SIDE FENCE


· Balastrade

Date:

- · Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

BACKYARD & SIDEYARD FENCE maximum height 6'0" Board Fence — wood or vinyl Block Wall — with plaster or stucco. Rock Wall — dark moss rock with dark colored grout.	Chainlink Fer Unfinished C street or ne
Purchaser's Signature:	

Date: Purchaser's Signature: Date:



- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight—line setback of the roadway, as indicated on the plan.

NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Fence Guideline Plan

for house at:

Model 4 Site 22

P.O. Box 2780 Kunia Residential Partners 650 Iwilei Rd. ROCK WALL PICKET FENCE BLOCK WALL OPEN RAIL SOLID BASE OPEN RAIL 5 CORNER FENCE **ELEVATIONS** NOT TO SCALE SIDEYARD TYPE "C" - maximum height 6'0" Board Fence — wood or vinyt
 Block Wall — with plaster or stucco.
 Rock Wall — dark moss rock with 80 š

ACCEPTABLE FENCE BUILDING MATERIALS

Honolulu, Hawaii

FRONT YARD FENCE maximum height 30"
Picket Fence — wood or viny!
Block Wall — with plaster or stucco
Rock Wall — dark moss rock with dark colored grout

TYPE "B" - maximum height 5'-0" · Open Rail

- · Open Rail with Solid Base lower portion up to 30° height
- Where stated on plan, total fence height may be 6'-0".

FENCE SYMBOL LEGEND - FRONT YARD FENCE CORNER LOT FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

Date: March 21, 2000

- Balastrade
- · Chainlink Fence or any Wire Mesh
- Unfinished CMU visible from the street or neghboring property

Seller's Signature:_ Purchaser's Signature: _ Date:_ Purchaser's Signature: __ Date: .


- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings ore to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or lence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent readway shall be placed within the sight— line setback of the roadway, as indicated on the plan.

F


BACK

Date:_

Seller's Signature:_



This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made. NOTE:




dark colored grout

Purchaser's Signature:_

Purchaser's Signature:_

· Unfinished CMU vitile from the street or neighboring property

Date: _



NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Fence Guideline Plan

TYPICAL LOT W/ RETAINING WALL

Lot 27/28

Model

Kunia Residential Partners 100 Kahelu Aye Mililani, Hawaii P.O. Box 898900 BLOCK WALL ROCK WALL FRONTYARD OR OPEN RAIL W/ OPEN RAIL 5 CORNER FENCE **ELEVATIONS** NOT TO SCALE BOARD FENCE BLOCK WALL ROCK WALL SIDEYARD F BACK

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- PRONI TARD FERGE
 maximum height 30"
 Picket Fence wood or vinyl
 Block Wall with plaster or stucco
 Rock Wall dark moss rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Rail

- Open Rail with Solid Base lower portion up to 30" height Where stated on plan, total
- fence height may be 6'-0"

BACKYARD & SIDEYARD FENCE


- BACKYARD & SIDETARD FENCE maximum height 6'0" * Board Fence wood or viny! * Block Wall with plaster or stucco. * Rock Wall dark moss rock with dark colored grout.

FENCE SYMBOL LEGEND ---- FRONT YARD FENCE - I - CORNER LOT FENCE BACK OR SIDE FENCE

Date: December 06, 1999

- Balastrade
- Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
Date:	Purchaser's Signature:	Date:



NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Kunia Residential Partners

Fence Guideline Plan

P.O. Box 898900

for house at:

Model Site Lot 29 Date: December 07, 1999

PICKET FENCE BLOCK WALL ROCK WALL OPEN RAIL 101 CORNER FENCE **ELEVATIONS** NOT TO SCALE BOARD FENCE BLOCK WALL ROCK WALL SIDEYARD F BACK

ACCEPTABLE FENCE BUILDING MATERIALS

100 Kahelu Ave Mililani, Hawaii

FRONT YARD FENCE maximum height 30"
Picket Fence — wood or vinyl
Black Wall — with plaster or stucca
Rack Wall — dark mass rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Roil

- Open Rail with Salid Base lower portion up to 30" height Where stated on plan, total
- fence height may be 6'-0".

UNACCEPTABLE FENCE BUILDING MATERIALS

- · Chainlink Fence or any Wire Mesh

FENCE SYMBOL LEGEND


---- FRONT YARD FENCE

CORNER LOT FENCE

· Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
Date:	Purchaser's Signature:	Date:

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight—line setback of the roadway, as indicated on the plan.



REAR YARD FENCING NOTES:

- FENCE WALLS SHOULD BE DESIGNED AND THE PLANS SHOULD BE STAMPED BY A CIVIL OR STRUCTURAL ENGINEER LICENSED IN THE STATE OF HAWAII.
- FENCE WALL FOOTING SHOULD NOT PENETRATE THE UNDERLYING GEOGRIDS.
 IN GENERAL, THE GEOGRIDS EXTEND LATERALLY FROM ABOUT 8 FEET BEYOND
 THE KEYSTONE WALL AND VERTICALLY ABOUT 16" INCHES BELOW THE TOP OF THE KEYSTONE WALL.
- FENCE WALL FOOTING SHOULD BE EMBEDDED DEEP ENOUGH FOR AN ADEQUATE HORIZONTAL SETBACK FROM THE SLOPE FACE.
- . FENCE WALLS SHOULD BE DESIGNED FOR CODE REQUIRED LOADS.

Honolulu, Hawaii

- THE SITE GRADE OF THE LOTS SHOULD NOT BE FAISED, AND THEREFORE, RETAINING WALLS SHOULD NOT BE CONSTRUCTED.
- . FOR MORE INFORMATION REFER TO GOELABS LETTER OF 02-16-00 DATE
- . TYPE 'C' WALL MAY BE USED.

NOTE:

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence Plan

for house at:

C Model Site 30 Date: March 15, 2000

P.O. Box 2780 Kunia Residential Partners 650 Iwilei Rd. ROCK WALL PICKET FENCE BLOCK WALL FRONTYARD OPEN RAIL 5 CORNER FENCE **ELEVATIONS** NOT TO SCALE BOARD FENCE BLOCK WALL ROCK WALL SIDEYARD Board Fence - wood or vinyl
Block Wall - with plaster or stucco.
Rock Wall - dark moss rock with S.

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE maximum height 30

- Picket Fence wood or vinyl Block Wall with plaster or stucco Rock Wall dark moss rock with dark colored grout

TYPE "B" - maximum height 5'-0" Open Rail

· Open Rail with Solid Base - lower

TYPE "C" - maximum height 6'0"

portion up to 30" height • Where stated on plan, total fence height may be 6'-0".


FENCE SYMBOL LEGEND - - FRONT YARD FENCE CORNER LOT FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- Chainlink Fence or any Wire Mesh
 Unfinished CMU visible from the street or neghboring property

Purchaser's Signature: _ Seller's Signature: Date: . Purchaser's Signature: _

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sightline setback of the roadway, as indicated on the plan.



REAR YARD FENCING NOTES:

- FENCE WALLS SHOULD BE DESIGNED AND THE PLANS SHOULD BE STAMPED BY A CIVIL OR STRUCTURAL ENGINEER LICENSED IN THE STATE OF HAWAII.
- FENCE WALL FOOTING SHOULD NOT PENETRATE THE UNDERLYING GEOGRIDS.
 IN GENERAL, THE GEOGRIDS EXTEND LATERALLY FROM ABOUT 8 FEET BEYOND.
 THE KEYSTONE WALL AND VERTICALLY ABOUT 16" INCHES BELOW THE TOP OF THE KEYSTONE WALL.
- FENCE WALL FOOTING SHOULD BE EMBEDDED DEEP ENOUGH FOR AN ADEQUATE HORIZONTAL SETBACK FROM THE SLOPE FACE.
- . FENCE WALLS SHOULD BE DESIGNED FOR CODE REQUIRED LOADS
- THE SITE GRADE OF THE LOTS SHOULD NOT BE RAISED, AND THEREFORE, RETAINING WALLS SHOULD NOT BE CONSTRUCTED.
- . FOR MORE INFORMATION REFER TO GOELABS LETTER OF 02-16-00 DATE.
- . TYPE 'C' FENCE MAY BE USED.

NOTE:

OR

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence Plan

for house at:

650 Iwilei Rd.

Model Site 31 / 32 Lot

P.O. Box 2780 Kunia Residential Partners FRONTYARD BLOCK WALL ROCK WALL PICKET FENCE 30 OPEN RAIL W/ SOLID BASE OPEN RAIL 5 CORNER FENCE **ELEVATIONS** NOT TO SCALE FENCE BLOCK WALL SIDEYARD

ACCEPTABLE FENCE BUILDING MATERIALS

- FRONT YARD FENCE maximum height 30"
 Picket Fence wood or viny!
 Block Wall with plaster or stucco
 Rock Wall dark moss rock with cark colored grout

Honalulu, Hawaii

TYPE "B" - maximum height 5'-0"

- · Open Rail
- · Open Rail with Solid Base lower portion up to 30" height
- Where stated on plan, total fence height may be 6'-0".

TYPE "C" - maximum height 6'0" TYPE C - maximum height 6 0

Board Fence - wood or vinyl

Block Woll - with plaster or stucco.

Rock Wall - dark moss rock with

FENCE SYMBOL LEGEND - - FRONT YARD FENCE CORNER LOT FENCE BACK OR SIDE FENCE

March 15, 2000


Date:


UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- Chainlink Fence or any Wire Mesh
- Unfinished CMU visible from the street or neghboring property

Seller's Signature:_ Purchaser's Signature: ___ Date: _ Purchaser's Signature: _ Date: _ Date:_

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight—line setback of the roadway, as indicated on the plan.





REAR YARD FENCING NOTES:
• REFER TO KAI HAWAI DRAWING 'S-1' FENCE POST FOOTINGS (01-25-00) AND FAX OF

- . FENCE POSTS SHALL ONLY BE INSTALLED TO PRE-INSTALLED FENCE FOOTINGS.
- . DO NOT USE CONTINOUS FOOTING WALLS SUCH AS BLOCK WALL OR ROCK WALL
- . FENCE MATERIAL SHOULD BE MNYL, WOOD OR OPEN RAILING WITH A MAXIMUM HEIGHT

NOTE:

SIDEYARD

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Fence Guideline Plan

for house at:

4

Model

Lot 34 / 35 / 36 Date: March 21, 2000

P.O. Box 2780 650 Iwilei Rd. Kunia Residential Partners BLOCK WALL ROCK WALL PICKET FENCE FRONTYARD I OPEN RAIL 5 CORNER FENCE **ELEVATIONS** NOT TO SCALE ROCK WALL TYPE "C" - maximum height 6'0"

ACCEPTABLE FENCE BUILDING MATERIALS

Honolulu, Hawaii

FRONT YARD FENCE maximum height 30"

Picket Fence — wood or vinyl

Block Wall — with plaster or stucco

Rock Wall — dark mass rock with dark colored grout

TYPE "B" - maximum height 5'-0" Open Rail

Open Rail with Solid Base — lower portion up to 30" height

Block Wall — with plaster or stucco.
Rock Wall — dark mass rock with


Where stated on plan, total fence height may be 6'-0".


FENCE SYMBOL LEGEND - - FRONT YARD FENCE CORNER LOT FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- · Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neghboring property

Purchaser's Signature: __ Seller's Signature:_ Date: _ Purchaser's Signature: _ Date:_





VINYL FENCE

REAR

NOTE:

ROYAL KUNIA

dark colored grout

TYPE "B" — maximum height 5'-0"
• Open Rail · Open Rail with Solid Base - lower

portion up to 30" height Where stated on plan, total fence height may be 6'-0".

TYPE "C" - maximum height 6'0"

UNACCEPTABLE FENCE BUILDING MATERIALS


Balastrade

· Chainlink Fence or any Wire Mesh · Unfinished CMU visible from the street or neghboring property

BACK OR SIDE FENCE

Seller's Signature:	Purchaser's Signature:	Date:
	Purchaser's Signature:	Date:

TRUE NORTH Scale: 1"= 20



FENCE GUIDELINE NOTES

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway about the research of shall be placed within the sight— line setback of the roadway, as indicated on the plan.

NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Kunia Residential Partners

Guideline Fence Plan

P.O. Box 898900


for house at:

CR. Model Site 38 Date: March 21, 2000

PICKET FENCE BLOCK WALL FRONTYARD

ROCK WALL

OPEN RAIL 2 CORNER FENCE **ELEVATIONS** NOT TO SCALE



ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

100 Kahelu Ave Mililani, Hawaii

FRONT YARD FENCE
maximum height 30"
• Placket Fence — wood or vinyt
• Block Wall — with plaster or stucco
• Rock Wall — dark mass rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"

- Open Roll
 Open Roll
 Open Roll
 Grand
 Open Roll
 Open Roll

TYPE B BACK OR SIDE FENCE

FENCE SYMBOL LEGEND


----- FRONT YARD FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- · Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Seller's Signature: Purchaser's Signature: _ Date:_

Purchaser's Signature:_ Date: Date:



- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall , or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30° above the finish grade of the adjacent roadway shall be placed within the sight— line setback of the roadway, as indicated on the plan.

NOTE:

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence Plan

for house at:

E Model Site 39

Kunia Residential Partners

P.O. Box 898900

100 Kahelu Ave Mililani, Hawaii

March 21, 2000 Date:

PICKET FENCE BLOCK WALL ROCK WALL FRONTYARD T OPEN RAIL W/ OPEN RAIL 101 CORNER **ELEVATIONS** NOT TO SCALE BOARD FENCE BLOCK WALL SIDEYARD ક

ACCEPTABLE FENCE BUILDING MATERIALS

- FRONT YARD FENCE maximum height 30 Picket Fence wood or viny! Block Wall with plaster or stucco Rock Wall dark moss rock with dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"

* Open Rail

- Open Rail with Solid Base lower

BACKYARD & SIDEYARD FENCE maximum height 6'0"

Board Fence — wood or viny

Block Wall — with plaster or stucco.

Rock Wall — dark mass rock with

- portion up to 30° height Where stated on plan, total
- fence height may be 6'-0".

FENCE SYMBOL LEGEND ---- FRONT YARD FENCE


CORNER LOT FENCE

BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- Chainlink Fence or any Wire Mesh
- Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
	Purchaser's Signature:	Date:



- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sightline setback of the roadway, as indicated on the plan.

NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Fence Plan

Guideline

for house at:


В Model Site 47

Kunia Residential Partners

P.O. Box 898900

100 Kahelu Ave Militani, Hawaii

Date: November 12, 1999



ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- FRONT YARD FENCE maximum height 30"
 Picket Fence wood or vinyt
 Block Wall with plaster or stucco
 Rock Wall dark mass rock with

dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Rail

- Open Roil with Solid Base lower portion up to 30" height Where stated on plan, total
- fence height may be 6'-0".

BACKYARD & SIDEYARD FENCE maximum height 6'0" * Board Fence — wood or vinyt * Block Woll — with plaster or stucco. * Rock Woll — dark moss rock with

- dark colored grout.


FENCE SYMBOL LEGEND ---- FRONT YARD FENCE - I - CORNER LOT FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- · Chainlink Fence or any Wire Mesh
- Unfinished CMU visible from the street or neighboring property

Purchaser's Signature: _ Date: Seller's Signature: Purchaser's Signature:. Date:_ Date: .

TRUE NORTH Scale: 1"= 20"



FENCE GUIDELINE NOTES

- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shored.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight— line setback of the roadway, as indicated on the plan.

NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Fence Plan

Guideline

for house at:


Model Site 48 ot

Kunia Residential Partners

P.O. Box 898900

100 Kahelu Ave Mililani, Hawaii

Date: November 12, 1999



ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- * Picket Fence wood or vinyl

 * Block Wall with plaster or stucco

 * Rock Wall dark moss rock with
- dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Rail


- · Open Rail with Solid Base lower portion up to 30" height Where stated on plan, total
- fence neight may be 6'-0"

- BACKYARD & SIDEYARD FENCE maximum height 6'0" =#

 * Board Fence wood or viny!


 * Block Wall with plaster or stucco.

 * Rock Wall dark mass rock with dark colored grout.



- Balastrade
- · Chainlink Fence or any Wire Mesh
- Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
Date:	Purchaser's Signature:	Date:



- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4-No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight—line setback of the roadway, as indicated on the plan.

NOTE:

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence

for house at:

Model BR Site 57

P.O. Box 898900 100 Kahelu Ave Kunia Residential Partners ROCK WALL PICKET FENCE BLOCK WALL OPEN RAIL SOLID BASE OPEN RAIL 107 CORNER FENCE **ELEVATIONS** NOT TO SCALE BOARD FENCE BLOCK WALL SIDEYARD F BACK

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

Mililani, Hawaii

FRONT YARD FENCE
maximum height 30"
Picket Fence — wood or vinyt
Block Wall — with plaster or stucco
Rock Wall — dark moss rock with
dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5-0 Open Rail

- Open Rail with Solid Base lower
- portion up to 30" height
- Where stated on plan, total fence height may be 6'-0".

BACKYARD & SIDEYARD FENCE maximum height 6'0" Board Fence – wood or vinyt Block Wall – with plaster or stucco. Rock Wall – dark mass rock with

- dark colored grout.


FENCE SYMBOL LEGEND ---- FRONT YARD FENCE - I - CORNER LOT FENCE BACK OR SIDE FENCE

March 15, 2000

Date:

- · Balastrade
- · Chainlink Fence or any Wire Mesh
- Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
Date:	Purchaser's Signature:	Date:



- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4. No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sightline setback of the roadway, as indicated on the plan.

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made. NOTE:



Guideline Fence Plan

for house at:

100 Kahelu Ave

DR Model 4 Site Lot 58

Kunia Residential Partners P.O. Box 898900 PICKET FENCE BLOCK WALL ROCK WALL FRONTYARD OPEN RAIL 5 CORNER FENCE ELEVATIONS NOT TO SCALE BOARD FENCE BLOCK WALL ROCK WALL SIDEYARD ~ BACK

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- FRONT YARD FENCE
 maximum height 30"
 Picket Fence wood or vinyl
 Block Wall with plaster or stucco
 Rock Wall dark moss rock with dark colored grout

Mililani, Hawaii

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Rail

- Open Rail with Solid Base lower
- portion up to 30" height Where stated on plan, total fence height may be 6"-0".

BACKYARD & SIDEYARD FENCE maximum height 6'0"

Board Fence — wood or vinyt

Block Wall — with plaster or stucco.

Rock Wall — dark mass rock with

- dark colored grout.


FENCE SYMBOL LEGEND ----- FRONT YARD FENCE - I - CORNER LOT FENCE BACK OR SIDE FENCE

March 15, 2000

Date:

- Balastrade
- · Chainlink Fence or any Wire Mesh
- Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
Date:	Purchaser's Signature:	Date:



- 1 The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight— line setback of the roadway, as indicated on the plan.

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made. NOTE:



Fence Guideline Plan

for house at:

В Model Site 59

Kunia Residential Partners

P.O. Box 898900

100 Kahelu Ave Militani, Hawaii Date: March 15, 2000

SE PICKET FENCE BLOCK WALL ROCK	WALL S
	E ATIONS SCALE
BOARD FENCE BLOCK WALL ROCK ON SIDE AVER OF	NAL TO SERVICE STATE OF THE SE

CCEPTABLE FENCE BUILDING MATERIALS

RONT YARD FENCE

- RON TARD FERRE Picket Fence wood or viny! Block Wall with plaster or stucco Rock Wall dark moss rock with
- dark colored grout

CORNER LOT—SIDE & BACKYARD FENCE naximum height 5'—0" Open Rail

- Open Rail with Solid Base lower portion up to 30" height Where stated on plan, total
- fence height may be 6'-0"

BACKYARD & SIDEYARD FENCE maximum height 6°0" • Board Fence — wood or viny • Block Wall — with plaster or stucco. • Rock Wall — dark mass rock with


- dark colored grout.

FENCE SYMBOL LEGEND ----- FRONT YARD FENCE CORNER LOT FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Purchaser's Signature: __ _ Date: _ Seller's Signature:_ Purchaser's Signature: _ Date: _ Date:



- The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- 4 No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight— line setback of the roadway, as indicated on the plan.

NOTE:

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence Plan

for house at:

		Model	В	
		Site	4	
Sensoner		Lot	69	
Date:	November 12,	1999	Six	.33

Kunia Residential Partners P.O. Box 898900 100 Kahelu Ave PICKET FENCE BLOCK WALL ROCK WALL FRONTYARD OPEN RAIL OPEN RAIL 101 CORNER FENCE 30 **ELEVATIONS** NOT TO SCALE BLOCK WALL ROCK WALL BOARD FENCE SIDEYARD F

ACCEPTABLE FENCE BUILDING MATERIALS

FRONT YARD FENCE

- * Picket Fence wood or vinyl

 * Block Wall with plaster or stucco

 * Rock Wall dark moss rock with dark colored grout

Mililani, Hawaii

CORNER LOT-SIDE & BACKYARD FENCE moximum height 5'-0"
• Open Rail

- Open Rail with Solid Base lower portion up to 30" height Where stated on plan, total
- fence height may be 5'-0".

BACKYARD & SIDEYARD FENCE

- Board Fence wood or vinyl
 Block Wall with plaster or stucco.
 Rock Wall dark moss rock with dark colored grout.


FENCE SYMBOL LEGEND ----- FRONT YARD FENCE CORNER LOT FENCE BACK OR SIDE FENCE

UNACCEPTABLE FENCE BUILDING MATERIALS

- Balastrade
- Chainlink Fence or any Wire Mesh
- · Unfinished CMU visible from the street or neighboring property

Purchaser's Signature: _ Seller's Signature:_ Date: . Purchaser's Signature: _ Date: _ Date:





- 1. The Fence Guideline Plan is diagrammatic. All walls and fences including footings are to be within the homeowner's property, unless by agreement with adjacent property owner that the ownership of the wall or fence is to be shared.
- 2. The Fence Guideline Plan shows the MAXIMUM boundary of each fence type. The homeowner may construct a fence of the type designated anywhere from the plane of the house to the maximum boundary line shown.
- 3. Fences shall be set back from sidewalks and pavings as shown.
- No wall, fence or any obstruction greater than 30" above the finish grade of the adjacent roadway shall be placed within the sight— line setback of the roadway, as indicated on the plan

NOTE:

F

BACK

This fence guideline plan and all information thereon including fencing and dimensions are provided for general information and are approximate and do not, and are not intended to, represent the actual final construction. No warranties, expressed or implied are being made.



Guideline Fence Plan for house at:

В Model Site

100 Kahelu Ave Militani, Hawaii

Lot Date: November 12, 1999

FENCE SYMBOL LEGEND

---- FRONT YARD FENCE

- - CORNER LOT FENCE

BACK OR SIDE FENCE

P.O. Box 898900 Kunia Residential Partners ROCK WALL PICKET FENCE BLOCK WALL FRONTYARD OPEN RAIL 2 CORNER FENCE **ELEVATIONS** NOT TO SCALE BOARD FENCE SIDEYARD BACKYARD & SIDEYARD FENCE maximum height 6'0"

Board Fence — wood or vinyt

Block Wall — with plaster or stucco.

Rock Wall — dark mass rock with dark colored grout.

ACCEPTABLE FENCE BUILDING MATERIALS

- FRONT YARD FENCE maximum height 30°
 Picket Fence wood or viny!
 Block Wall with plaster or stucco
 Rock Wall dark mass rock with
- dark colored grout

CORNER LOT-SIDE & BACKYARD FENCE maximum height 5'-0"
• Open Rail

- Open Rail with Sciid Base lower portion up to 30" neight Where stated on pian, total fence height may be 6"-0".

- · Balastrade
- · Chainlink Fence or any Wire Mesh
- . Unfinished CMU visible from the street or neighboring property

Seller's Signature:	Purchaser's Signature:	Date:
Date:	Purchaser's Signature:	Date: